



Amarr 3582 with Champagne Pearl finish and Clear glass

Aluminum MultiView Doors

Amarr® 3582

Amarr 3582 Aluminum MultiView doors make a unique design statement with the widest single piece of glass that specifications, safety, and reliability standards allow. Constructed of 2" thick extruded aluminum rails and stiles, these doors are built to last. The **ClearView Aluminum Strut System** provides strength and durability without restricting the viewing area. With a wide selection of glass, acrylic and polycarbonate glazing options, in more than two dozen paint and anodize finishes, the Amarr 3582 is a distinctive choice for any building where style and functionality are important.




Amarr 3582 with Champagne Pearl (PVDF) frame and Clear glass.

CONSTRUCTION

Amarr 3582

MultiView Aluminum door

- 2" thick extruded aluminum rails & stiles
- Tongue and groove section joints provide additional protection against the elements
- Equal glass heights in all sections of a door
- Glass expands up to 8'2" wide



Track: All Amarr doors are available with both 2" or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow the Roof Pitch. Custom track configurations are also available. For drawings and more information, please visit www.amarr.com.

Springs: Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

Hardware: Amarr hardware includes minimum 14-gauge galvanized steel hinges and 13-gauge galvanized steel track brackets. All rollers have minimum 10-ball bearings.

SPECIFICATIONS

Amarr 3582	
MATERIAL	Aluminum
CONSTRUCTION LAYERS	Single
DOOR THICKNESS	2" (5.1cm)
SECTION HEIGHTS¹	Varies by door height
MINIMUM DOOR WIDTH	2' 0"
MAXIMUM DOOR WIDTH	20' 2" (in 1" increments)
MINIMUM DOOR HEIGHT¹	6' 0"
MAXIMUM DOOR HEIGHT¹	20' 1"
CLEARVIEW STRUT SYSTEM	Only required for doors ≥ 16'
WIND LOAD² AVAILABLE	NA
FINISH WARRANTY³	5 Years
WORKMANSHIP/HARDWARE WARRANTY³	1 Year
GLASS WARRANTY³	1 Year

¹ For complete section and door height configuration charts, visit amarr.com or contact your local Amarr dealer.

² It is your responsibility to make sure your garage door meets local building codes.

³ For complete warranty details, visit amarr.com or contact your local Amarr dealer.

GLAZING OPTIONS

	Single Pane										Insulated		
	Tempered				Laminated	Polycarbonate			Acrylic			Tempered	
	3/16"	3/16" Low-E	1/4"	1/4" Low-E		Single 1/8"	Single 1/4"	Tri-Wall 5/8"	1/8"	1/4"	1/2"	1/2"	1/2" Low-E
CLEAR	STD	•	•	•	•	•	•	•	•	•	•	•	•
OBSCURE	•											•	•
GRAY	•											•	•
BRONZE	•							•				•	•
GREEN	•											•	•
FROST	•		•					•				•	
SNOW					•			•					
WHITEOUT					•								
BLACK ICE					•								

DOOR CONFIGURATIONS

For Single Pane Glazing			Up to 8'2" Wide - 1 Panel	8'3"-16'2" Wide - 2 Panels
Door Width	# Center Stiles	# Windows/Section		
Up to 8'2"	0	2		
8'3" - 16'2"	1	4		
16'3" - 20'2"	2	6		

For Insulated Glazing			Up to 10'2" Wide - 2 Panels	10'3"-16'2" Wide - 3 Panels
Door Width	# Center Stiles	# Windows/Section		
Up to 10'2"	1	4		
10'3" - 16'2"	2	6		
16'3" - 20'2"	3	8		

ENTREMATIC

Entrematic
165 Carriage Court
Winston-Salem, NC 27105
800.503.D00R
www.amarr.com



Door specifications and technical data subject to change without notice.

Sectional door products from Entrematic may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents.

Entrematic and Amarr as words and logos are registered trademarks owned by Entrematic Group AB or companies within the Entrematic Group.

©Entrematic Group AB 2017. All rights reserved.
Printed in USA Form #6230317/15M/GVS